



SOLUTION OVERVIEW

- Distributed architecture: platform optimized for handling high volume IP traffic
- Store-to-Disk (S2D) capabilities: support packet capture at rates up to 10 Gbps

GeoProbe® G10

High Performance Support for High Capacity, High Bandwidth Networks

Hardware Platform Addresses Dynamic Changes in Network Traffic Composition

With a proven track record and worldwide deployment by Tier 1 operators, the GeoProbe family remains at the center of NETSCOUT's network monitoring portfolio. In keeping with the pace of network technology changes and dynamic market conditions, NETSCOUT has evolved its hardware to meet changing customer needs.

Designed specifically to address high bandwidth interfaces and data center applications, the NEBS-compliant GeoProbe G10 platform features a distributed architecture optimized to handle high volume IP traffic with native support for both IPv4 and IPv6.

The G10 serves as a primary collection and correlation agent for NETSCOUT's Service Assurance solution. Used to feed Iris applications, the G10 may be deployed in combination with existing Splrobes to provide a comprehensive view of the network.

Networking Requirements

Three connections and associated IP addresses

Interface Support

- 10G: 10Gbase-SR (850nm, multi-mode) and 10Gbase-LR (1310nm, single-mode)
- 1G: 1000base-SX (850nm, multi-mode) and 1000base-LX (1310nm, multi-mode or single mode), and 1000base-T (RJ-45, cat5)
- All optical ports are LC-type connectors

Protocol Support

- Mobile data and data center protocols: Gn/Gi, IuBC
- Next-generation 4G network protocols: LTE/EPC
- Multimedia and convergence protocols: VoIP/IMS

Rackmount Requirements

With a 3U footprint, the chassis is available for 4-post and center-post (19- or 23-inch) rack type mounting with supplied hardware.

Power Consumption

600W max, -40 to -72 VDC (15A max), 430W typical

Storage Subsystem

The storage subsystem enables the storage of packets and associated application data. Storage duration can be engineered based on bandwidth and storage type.

Default settings enable the storage of all packets, for all protocols. To provide maximum utility and efficient use of disk capacity, users have full control in limiting packet storage by specific protocols. Users can also define whether those selected packets will be stored with or without truncation.

Subsystem Components

- 900 GB SAS technology
- 4 TB Nearline SAS technology
- 2U controller and expansion enclosures
- Data storage: RAID 0 or RAID 5
- DC Power (AC available)

Power Consumption*

500W max, -40 to -72 VDC (12.5A max)

Recommended Cabling

12 AWG or larger cable for power and chassis ground (applies to both disk array and G10)

**Actual power consumption will be affected by the number of disks used.*

GeoProbe G10

The G10 is comprised of purpose-specific connection, processing and application boards and I/O ports. G10 supports 8 physical Ethernet connections (10G or 1G), up to four of which may be 10G. An uplink port on the application blade serves as the primary network interface while Operations, Administration and Maintenance (OAM) interfaces provide connectivity to Shelf Management Modules.

Productivity Features

Store-to-Disk (S2D)

G10 streams traffic directly to disk at configurable raw packet capture rates of up to 10 Gbps.

Low-Touch Installation, Configuration and Maintenance

G10 supports automated workflows to facilitate installation and configuration tasks. Scheduled group downloads streamline maintenance windows and ensure upgrade integrity with built-in reversibility commands. All configuration changes are logged with user ID, machine ID and relevant timestamps.

Stability Statistics

G10's throughput, disk utilization/health and disk wrap times are proactively monitored with threshold alarms for early notification and system administrator intervention.

Administrative Tools

G10 identifies unknown IP addresses not already configured in OAM topology. Log file information includes reporting interval, instrumentation name, IP address, protocol and total number of times a packet was sent or received by the IP address.

NETSCOUT

Americas East

310 Littleton Road
Westford, MA 01886-4105
Phone: 978-614-4000
Toll Free: 800-357-7666

Americas

3033 W. President
George Bush HGWY
Plano, Texas
USA 75075

EMEA

One Thames Valley
Wokingham Road
Bracknell, Berkshire
RG42 1NG

APAC

238A Thomson Road #23-02/05
Novena Square Tower A
Singapore
307684 SG

NETSCOUT offers sales, support, and services in over 32 countries.

For more information, please visit www.netscout.com or call us at 1-800-833-9200 option 1 or +1-469-330-4000

© 2016 NETSCOUT SYSTEMS, INC. All rights reserved. NETSCOUT, nGenius, InfiniStream, Sniffer, nGeniusONE, ASI, Adaptive Service Intelligence and the NETSCOUT logo are registered or pending trademarks of NETSCOUT SYSTEMS, INC. and/or its affiliates in the United States and/or other countries ("NETSCOUT"). All other brands and product names are registered and unregistered trademarks are the sole property of their respective owners. Use of this product is subject to the NETSCOUT SYSTEMS, INC. ("NETSCOUT") End User License Agreement that accompanies the product at the time of shipment or, if applicable, the legal agreement executed by and between NETSCOUT and the authorized end user of this product ("Agreement"). NETSCOUT reserves the right, at its sole discretion, to make changes at any time in its technical information, specifications, service, and support programs.