

InfiniStreamNG 2600 Appliance

HIGHLIGHTS

- Provides storage capacity of 16TB per appliance
 - Supports NETSCOUT's suite of Service Assurance applications
 - Designed for smaller scale environments
-

InfiniStreamNG Platform Overview

The InfiniStreamNG™ platform represents the next evolution of NETSCOUT's high capacity and flexible appliances that leverage Adaptive Service Intelligence™ (ASI) technology to perform deep packet capture and analysis of services, service enablers and network performance. Offering unsurpassed scalability, InfiniStreamNG probes are integrated with the nGeniusONE® Service Assurance platform to provide a common set of packet-flow-based metadata for use in troubleshooting, service and application performance, detailed key performance indicators, as well as real-time and historical forensic analysis. NETSCOUT® offers multiple InfiniStreamNG models (appliance, COTS-based software and virtual appliances) to support the different processing and storage needs of enterprise and service provider environments including business services, mobile, fixed-line voice, residential triple-play, satellite and cable/MSO networks.

InfiniStreamNG 2600 Overview

The InfiniStreamNG 2600 appliance is ideal for smaller capacity 1/10 Gigabit monitoring requirements at the edge of the network. With a storage capacity of 16TB, InfiniStreamNG 2600 probes can be used to efficiently capture traffic in branch offices and in departmental network segments.

Deployment

Strategically deployed throughout the network, InfiniStreamNG 2600 appliances balance processing power, packet capture performance and data storage appropriate for network segments closer to users and customers, where traffic volumes may be lower but application performance is just as critical to business success. InfiniStreamNG 2600 appliances present real-time views of end-to-end call trace data and network-wide KPI visibility, to protect the reliability and availability of networks and services.



2695 | 16TB, 4 Port 1/10 GbE SFP+

SPECIFICATIONS

InfiniStreamNG 2600 Appliance

| | |
|---------------------------------|---|
| Packet Capture Ports | 4 Port 1/10 GbE SFP/SFP+ |
| Management Port | 2 RJ-45 1/10GBASE-T 1 IPMI 1000BASE-T |
| Storage | 16TB (RAID 6) |
| Embedded OS | Solid State Drive (SSD) dedicated to Linux® OS |
| Rack Unit | 1 Rack Unit (1RU) |
| Dimensions | 1.7 in (43 mm) Height 17.2 in (437 mm) Width 25.6 in (650 mm) Depth |
| Weight | 38 lbs (17.24 kg) |
| Mounts | Rack mount side rails included |
| Power Rating (AC) | 1+1 hot-swappable, redundant 700W: 100-140 VAC, 50-60 Hz, 8.0-6.0 Amp 750W: 180-240 VAC, 50-60 Hz, 4.5-3.8 Amp |
| Maximum Consumption (C) | 5.6A, 557W |
| Heat Dissipation (AC) | 1900 BTU/Hr |
| Power Rating (DC) | 1+1 hot-swappable, redundant -48VDC, 650W, 20A (x2) |
| Maximum Consumption (DC) | 12A, 565W |
| Heat Dissipation (DC) | 1928 BTU/Hr |
| Vibration | 0.25G from 5-200Hz for 15 minutes |
| Operating Temperature | 41° to 95°F (5° to 35°C) |
| Operating Humidity | 8% - 90% (non-condensing) |
| Altitude | -50 to 10,000 ft (-16 to 3,048 m) |
| Mechanical Shock | 1 shock pulse up to 20G for up to 2.5 ms |
| Regulatory Approvals | Model Number: NV41U, FCC Part 15 Class A, CE Mark (EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3), VCCI(Japan) Class A, RCM (Australia), RRA (Korea) KC Cert #: KCC-REM-NSZ-NV41U, UL 60950-1, CAN/CSA C22.2 No.60950, IEC 60950-1, EN 60950-1, CB Report, UL-GS (DEMKO) |

nGeniusONE Platform

The nGeniusONE Service Assurance platform provides insights into the performance characteristics of data, voice and video service delivery to manage the availability and quality of the user's experience. nGeniusONE helps dramatically shorten the time required to solve network and application performance issues by providing a common set of metadata for service visibility across network elements, applications and devices to address the needs of network and IT operations teams.

ASI Technology



NETSCOUT's patented, ASI technology is a next generation Deep Packet Inspection (DPI) engine that intelligently and efficiently analyzes packet and flow data to provide real-time, contextual analysis of service, network and application performance. ASI provides an unparalleled wealth of information and uses sophisticated algorithms that determine the best way to process, store and retrieve data, guaranteeing that InfiniStreamNG probes make the most efficient use of compute and storage resources.

NETSCOUT®

Americas East

310 Littleton Road
Westford, MA 01886-4105
USA
Phone: 978-614-4000
Toll Free: 800-357-7666

Americas

3033 W. President
George Bush Hwy
Plano, TX 75075-5752
USA

APAC

238A Thomson Road, #25-04/05
Novena Square Tower A
Singapore 307684

EMEA

One Thames Valley
Wokingham Road
Bracknell, Berkshire
RG42 1NG
UK

NETSCOUT offers sales, support, and services in over 32 countries.

For more information, please
visit www.netscout.com or
call us at 1-800-833-9200 option 1
or +1 469-330-4000

© 2016 NETSCOUT SYSTEMS, INC. All rights reserved. NETSCOUT, nGenius, InfiniStream, InfiniStreamNG, nGeniusONE, ASI, Adaptive Service Intelligence and the NETSCOUT logo are registered or pending trademarks of NETSCOUT SYSTEMS, INC. and/or its affiliates in the United States and/or other countries ("NETSCOUT"). All other brands and product names and registered and unregistered trademarks are the sole property of their respective owners. Use of this product is subject to the NETSCOUT SYSTEMS, INC. ("NETSCOUT") End User License Agreement that accompanies the product at the time of shipment or, if applicable, the legal agreement executed by and between NETSCOUT and the authorized end user of this product ("Agreement"). NETSCOUT reserves the right, at its sole discretion, to make changes at any time in its technical information, specifications, service, and support programs.